




Stossverbinder KST, 10mm² bis 500mm²

- Material: Cu 99,95 %, Cu verzinkt (Cu/Sn).
- Sichtloch und Kabelstopp.
- Für mehrdrähtige (Klasse 2) Cu-Leiter.
- UL-zertifiziert (1-500 mm²)
DNV-zertifiziert (16-400 mm²).



| Artikelnummer | Leiterquerschnitt mm ² | Cu AWG/MCM | d | D | L | s | Pressbacken-Nr. |
|---------------|-----------------------------------|------------|------|-----|-----|----|-----------------|
| KST10 | 10 | 8 | 4,5 | 7 | 30 | 15 | 7 |
| KST16 | 16 | 6 | 5,5 | 8,5 | 35 | 17 | 8,5 |
| KST25 | 25 | 4 | 7 | 10 | 40 | 20 | 10 |
| KST35 | 35 | 2 | 8,5 | 12 | 45 | 22 | 12 |
| KST50 | 50 | 1/0 | 10 | 14 | 50 | 25 | 14 |
| KST70 | 70 | 2/0 | 12 | 16 | 55 | 27 | 16 |
| KST95 | 95 | 4/0 | 13,5 | 18 | 60 | 30 | 18 |
| KST120 | 120 | 250 | 15 | 19 | 60 | 30 | 19 |
| KST150 | 150 | 300 | 17 | 22 | 65 | 32 | 22 |
| KST185 | 185 | 350 | 19 | 24 | 75 | 37 | 24 |
| KST240 | 240 | 500 | 21 | 26 | 85 | 42 | 26 |
| KST300 | 300 | 600 | 24 | 30 | 90 | 45 | 30 |
| KST400 | 400 | 750 | 26 | 32 | 90 | 45 | 32 |
| KST500 | 500 | 1000 | 31 | 40 | 135 | 68 | 40 |